



1511 Hancel Parkway Mooresville, IN 46158 317-837-2444

## Seat Rail Extender Kit 1999-2004 Mustangs (SRX-M01)

Don't be cramped when putting your horse through it's' paces! Installing our Seat Rail Extenders repositions the seat 4" further to the rear, providing tall drivers and passengers additional legroom. Like all **Innovative Performance Technologies** products, this kit is designed for functionality, appearance and ease of installation; but more importantly, manufactured to a quality level that is second to none. Requires one kit per seat.

### Kit Includes:

- 2 Seat Rail Extender
- 2 1-hole Backing Plates
- 4 10x1.5-40mm Hex Head Bolts
- 6 10x1.5 Nyloc Nuts
- 2 spacers

10 3/8 Washers

**Required Tools:** Basic hand tools  
Drill and 13/32" bit

**Install Time:** Approximately 2 hrs.

*(Please read all instructions prior to beginning installation. Contact your dealer with any questions.)*

### Installation:

1. Remove seat from vehicle. Keep all mounting hardware, as some will be re-used during installation process.
2. Position front hole of Seat Rail Extender over factory stud and loosely secure to floor re-using factory hardware.
3. Place 10mm bolt, washer and spacer as shown in Fig.1 and fasten into rear factory mounting hole. Tighten both front and rear bolts securely.
4. Repeat procedure for second rail.
5. Re-install seat and position front seat track mounting hole over second hole located in Seat Rail Extender. Using the factory bolt removed from rear mounting location, insert bolt and washer from top side and loosely secure with supplied nut and washer. Repeat for second rail.
6. Slide seat forward on tracks to access the rear mounting location.
7. Using rear hole in the Seat Extender Rail and seat track as a guide, drill through the floor pan with a 13/32" drill bit. **Note:** Before drilling, confirm area is clear on bottom side of car.
8. Using supplied hardware, insert 10mm bolt and washer from above and secure with backing plate, washer and nyloc nut under car. Repeat for second rail and tighten all bolts securely.



SRX-M01

[www.BuyStifflers.com](http://www.BuyStifflers.com)

Page 1